



**Specification**

Product Code	OZ1BC	OZ2BC	OZ3BC	OZ5BC	OZ10BC
Safe Working Load (lbs)	2,000 (lbs)	4,000 (lbs)	6,000 (lbs)	10,000 (lbs)	20,000 (lbs)
Adjustable Flange Width (in)	2.95-9.05 (in)	2.95-9.05 (in)	3.15-12.60 (in)	3.54-12.60 (in)	3.54-12.60 (in)
Dimensional Information (in)	A	10.94 (in)	10.94 (in)	14.01 (in)	14.01 (in)
	B	7.16-14.96 (in)	7.16-14.96 (in)	8.66-19.68 (in)	8.66-19.68 (in)
	C	2.51 (in)	2.91 (in)	3.94 (in)	4.41 (in)
	D	.16 (in)	.24 (in)	.31 (in)	.39 (in)
	E	8.54 (in)	8.54 (in)	10.90 (in)	10.90 (in)
	F	3.54-5.90 (in)	3.54-5.90 (in)	5.71-8.66 (in)	5.71-8.66 (in)
	G	1.02 (in)	1.02 (in)	1.97 (in)	1.85 (in)
	H	.75 (in)	.83 (in)	.90 (in)	1.14 (in)
Net Weight (lbs)	9 (lbs)	10 (lbs)	21 (lbs)	25 (lbs)	35 (lbs)