



Specification

Product Code	OZ05PBT	OZ1PBT	OZ2PBT	OZ3PBT	OZ5PBT	OZ10PBT	
Safe Working Load (lbs)	1,000 (lbs)	2,000 (lbs)	4,000 (lbs)	6,000 (lbs)	10,000 (lbs)	20,000 (lbs)	
Adjustable Flange Width (in)	2.52-5.90 (in)	2.52-8.00 (in)	3.46-8.00 (in)	4.00-8.00 (in)	4.49-8.00 (in)	4.92-8.00 (in)	
Dimensional Information (in)	A	10.00 (in)	12.52 (in)	13.19 (in)	14.05 (in)	14.49 (in)	15.94 (in)
	B	8.50 (in)	10.24 (in)	11.81 (in)	13.58 (in)	15.55 (in)	17.91 (in)
	C	7.67 (in)	9.41 (in)	11.26 (in)	13.23 (in)	15.47 (in)	19.68 (in)
	H	4.33 (in)	5.31 (in)	6.34 (in)	7.28 (in)	8.66 (in)	11.02 (in)
Minimum Radius Curve (ft)	2.95 (ft)	3.28 (ft)	3.60 (ft)	4.26 (ft)	4.59 (ft)	5.57 (ft)	
Net Weight (lbs)	20 (lbs)	32 (lbs)	50 (lbs)	82 (lbs)	123 (lbs)	215 (lbs)	